


# IMB-791

## ATX Motherboard



### Spotlight Features

- Socket LGA1151 for Intel® Core i7/i5/i3/Celeron (Skylake-S)
- Intel® Gen9 Intel® Graphics DX 11/12, OGL4.3/4.4
- Supports Dual Channel DDR4 2133MHz, 2 x Long-DIMM, up to 32GB system memory
- 1 x VGA, 3 x Displayport
- 4 xUSB 3.0, 5 x USB 2.0, 4 x SATA3
- 1 x PCIe x16, 1 x PCIe x1, 3 x PCI, 1 x PCIe x4 Slot , 1 x mSATA
- Gigabit LAN : 1 x Intel LAN
- 1 x TPM Header
- ATX PWR Con (24+8-pin)

### Specifications

Processor System	
Dimension	ATX (12-in x 9.6-in)
CPU	Socket LGA1151 for Intel® Core i7/i5/i3/Celeron(Skylake-S)
Core Number	(By CPU, Max 4)
Max Speed	(By CPU)
L2 Cache	(By CPU)
Chipset	Intel® H110
BIOS	UEFI
Expansion Slot	
PCIe	1 x PCIe x16, 1 x PCIe x1, 3 x PCI, 1 x PCIe x4 slot
Mini PCIe	0
M.2	0
mSATA	1
Memory	
Technology	Dual Channel DDR4 2133MHz
Max.	32GB
Socket	2 x Long-DIMM
Graphics	
Controller	Intel® Gen9 Graphics DX 11/12, OGL4.3/4.4
VRAM	Shared Memory
VGA	Supports max resolution up to 1920 x 1200
LVDS	No
eDP	No
HDMI	No
DVI	No
DisplayPort	Supports max resolution up to 4096 x 2160@60Hz
Multi Display	Yes (Dual Display)
Ethernet	
Interface	10/100/1000 Mbps
Controller	1 x Intel I219V
Connector	1 x RJ45
SATA	
Max Data Transfer Rate	SATA3 (6.0Gb/s)

Rear I/O	
VGA	1
DVI	0
HDMI	0
DisplayPort	3
Ethernet	1
USB	4 x USB 3.0
Audio	3 (Mic-in, Line-in, Line-out)
Serial	2 x COM (1 x RS-232, 1 x RS-232/422/485)
PS/2	1 x PS/2 combo
Internal Connector	
USB	5 x USB 2.0 (2 x 2.54 pitch header, 1 x USB2.0 Type-A vertical con)
LVDS/inverter	0/0
eDP	0
VGA	0
Serial	2 x COM (supports RS-232 only)
SATA	4 (one shared with mSATA)
mPCIe	0
Parallel	1
mSATA	1
IrDA	0
GPIO	8 x GPI + 8 x GPO
SATA PWR Output Con	1
Speaker Header	1
Watchdog Timer	
Output	From Super I/O to drag RESETCON#
Interval	256 segments, 0,1,2...255sec/min
Power Requirements	
Input PWR	ATX PWR Con (24+8-pin)
Power On	AT/ATX Supported AT : Directly PWR on as power input ready ATX : Press button to PWR on after power input ready
Environment	
Operating Temperature	0°C – 60°C