


NANO-BT-i1

EPIC SBC supports Intel® 22nm Atom™/Celeron® on-board SoC with VGA, HDMI, LVDS, Dual Intel® PCIe GbE, USB 3.0, Dual PCIe Mini, SATA 6Gb/s, mSATA, COM, Audio and RoHS



Specifications

- ◆ SoC
 - Intel® Atom™ E3845 on-board SoC (1.91GHz, quad-core, 2MB cache, TDP=10W)
 - Intel® Atom™ E3827 on-board SoC (1.75GHz, dual-core, 1MB cache, TDP=8W)
 - Intel® Atom™ E3826 on-board SoC (1.46GHz, dual-core, 1MB cache, TDP=7W)
 - Intel® Atom™ E3825 on-board SoC (1.33GHz, dual-core, 1MB cache, TDP=6W)
 - Intel® Atom™ E3815 on-board SoC (1.46GHz, single-core, 512KB cache, TDP=5W)
 - Intel® Celeron® J1900 on-board SoC (2GHz, quad-core, 2MB cache, TDP=10W)
 - Intel® Celeron® N2930 on-board SoC (1.83GHz, quad-core, 2MB cache, TDP=7.5W)
 - Intel® Celeron® N2807 on-board SoC (1.58GHz, dual-core, 2MB cache, TDP=4.3W)
- ◆ BIOS
 - AMI UEFI BIOS
- ◆ Memory
 - One 204-pin 1066/1333MHz single-channel unbuffered DDR3L SDRAM SO-DIMM supports up to 8 GB (J1900, N2930, E3845, E3827, E3826) or 4 GB (N2807, E3825, E3815)
- ◆ Graphics Engine
 - Intel® HD Graphics Gen 7 Engines with 4 execution unit, supports DX11.1, OpenGL 4.2 and OpenCL1.2
- ◆ Display Output
 - VGA (up to 2560x1600@60Hz)
 - HDMI (up to 2560x1600@60Hz)
 - 18/24-bit dual-channel LVDS by CH7511B DP to LVDS converter (up to 1920x1200@60Hz)
- ◆ Ethernet
 - LAN1: Intel® I210-AT PCIe controller with NCSI support
 - LAN2: Intel® I211-AT PCIe controller
- ◆ Super I/O
 - Fintek F81866
- ◆ I/O Interface
 - 2 x SATA 3Gb/s with 5V SATA power connector (no RAID)
 - 1 x USB 3.0 (on rear I/O)
 - 1 x RS-422/485 (pin header)
 - 1 x PS/2 KB/MS
 - 3 x USB 2.0 (1 on rear I/O, 2 by pin header)
 - 3 x RS-232 (pin header)
 - 1 x Micro SD slot (E38XX SKU only)
- ◆ iRIS Remote Management Module
 - 1 x iRIS-1010 slot
- ◆ SMBus
 - 1 x 4-pin (1x4) wafer
- ◆ Audio
 - Realtek ALC662 HD Audio codec
 - 1 x Analog audio by 10-pin (2x5) header
- ◆ Front Panel
 - 1 x 6-pin (1x6) wafer for power LED & HDD LED
 - 1 x 2-pin (1x2) wafer for power button
 - 1 x 2-pin (1x2) wafer for power reset
- ◆ LAN LED
 - 2 x 2-pin headers for LAN1 Link LED, LAN2 Link LED
- ◆ Expansion
 - 1 x Full-size PCIe Mini card slot (support mSATA co-lay SATA port 2)
 - 1 x PCI/104 slot (PCI signal)
- ◆ Digital I/O
 - 8-bit digital I/O (4-bit input, 4-bit output)
- ◆ Fan Connector
 - 1 x 3-pin CPU fan connector
 - 1 x 3-pin system fan connector
- ◆ Power supply
 - 12V only DC input
 - 1 x Internal 4-pin (2x2) power connector
 - Support AT/ATX mode
- ◆ Power Consumption
 - +12V@1.52A (Intel® Atom™ Processor J1900 CPU, 1 x 8GB 1333 MHz DDR3 memory)
- ◆ Watchdog Timer
 - Software programmable, support 1~255 sec. system reset
- ◆ Operating Temperature: -20°C ~ 60°C
- ◆ Storage Temperature: -30°C ~ 70°C
- ◆ Operating Humidity: 5% ~ 95%, non-condensing
- ◆ Dimensions: 115mm x 165mm
- ◆ Weight: GW:850g / NW:350g

Highly efficient and power optimized multi-format codec engine



- ◆ Full HW Acceleration for Video Decode
 - H.264, VC1 MPEG2, MVC, VP8, MPEG-4/H.263
 - MJPEG formats


Bay Trail SoC



- ◆ Video Encode
 - » Full HW acceleration for H.264
 - » Hybrid HW acceleration of MPEG2



Bay Trail SoC



Features

1. EPIC SBC supports Intel® 22nm Atom™ or Celeron® on-board SoC
2. Supports dual independent display with LVDS, VGA and HDMI
3. 1.35V DDR3L 1333/1066 MHz SDRAM support up to 8GB
4. Support IPMI 2.0 with iRIS-1010 module
5. IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Packing List

1 x NANO-BT single board computer with heatsink	
2 x SATA with power cable kit (P/N: 32801-000201-300-RS)	
2 x RS-232 cable (P/N: 19800-000300-200-RS)	
1 x Power cable (P/N: 32100-087100-RS)	1 x QIG (Quick Installation Guide)
1 x One Key Recovery CD	1 x Utility CD

Ordering Information

Part No.	Description
NANO-BT-i1-J19001-R10	EPIC SBC supports Intel® 22nm quad-core J1900 2.0GHz (10W) on-board SoC with VGA/HDMI/LVDS, Dual PCIe GbE, USB 3.0, PCIe Mini, SATA 3Gb/s, mSATA, COM, iRIS-1010, Audio and RoHS
NANO-BT-i1-N29301-R10	EPIC SBC supports Intel® 22nm quad-core N2930 1.83GHz (7.5W) on-board SoC with VGA/HDMI/LVDS, Dual PCIe GbE, USB 3.0, PCIe Mini, SATA 3Gb/s, mSATA, COM, iRIS-1010, Audio and RoHS
NANO-BT-i1-N28071-R10	EPIC SBC supports Intel® 22nm dual-core N2807 1.58GHz (4.3W) on-board SoC with VGA/HDMI/LVDS, Dual PCIe GbE, USB 3.0, PCIe Mini, SATA 3Gb/s, mSATA, COM, iRIS-1010, Audio and RoHS
NANO-BT-i1-E38XX1-R10**	EPIC SBC supports Intel® Atom™ E38XX on-board SoC with VGA/HDMI/LVDS, Dual PCIe GbE, USB 3.0, PCIe Mini, SATA 3Gb/s, mSATA, COM, iRIS-1010, Audio and RoHS (by project support, MOQ 100pcs/lot)
iRIS-1010-R10	IPMI 2.0 adapter card with AST1010 BMC chip (W/O KVM over IP function) for PCIe Mini socket interface
32006-000300-100-RS	PS/2 KB/MS Y-cable without bracket
32000-070301-RS	Dual-port USB 2.0 cable
32205-003800-300-RS	RS-422/485 cable, 200mm

** : Those item are by order production, MOQ: 100