

Mini-PCI Video Capture Card

H.264 Hardware compression

MP-6100

4-ch Video & Audio inputs , 8-bit GPIO

Support D1 & CIF resolution

Windows Directshow compatible

Windows & Linux SDK provided

Network Streaming SDK provided



Form Factor	Mini-PCI Type-III B
Compression Format	H.264 Hardware compression technology
Video	Inputs : 4 channel
	Connector Type : BNC connector
	Display Rate : 1-ch : Total 30 fps / D1 resolution 4-ch : Total 120 fps / CIF resolution
	Recording Rate : 1-ch : Total 30 fps / D1 resolution 4-ch : Total 120 fps / CIF resolution
Audio	Inputs : 4 channel
	Connector Type : RCA connector (Cable for optional)
GPIO	8-bit GPIO interface
OS Support	Windows XP , Linux (Ubuntu 8.04 or Kernel 2.6.27)
Software	Windows SDK (Directshow support) , Linux SDK , Network Streaming SDK
Cable kit	1 x 10-pin header to D-sub 9 Cable & 1 x 4-Ch Video input (BNC connector) Cable Option 1 x 10-pin header to D-sub 9 Cable & 1 x 4-ch Audio (RCA connector) cable
Dimensions (L x W)	60mm x 45mm
Ordering Code	
MP-6100	4-ch H.264 Video & Audio Mini-PCI capture Card with SDK provided (option)1 x 10-pin header to D-sub 9 Cable & 1 x 4-ch Audio (RCA connector) cable

For further product information please visit the website at <http://www.commell.com.tw>

Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw

COMMELL

Stage For Your Success