



Key Features

- 15" Intel Core i7/i5 Fanless Stainless Panel PC
- IP66 full sealed with Anti-corrosion enclosure
- 15" LCD with full flat Resistive touch
- IP67 M12 metal connectors
- Special inspection of 100% waterproof guarantee
- CE, FCC, VCCI Class B certified
- Optional Mini-PCle WLAN with external antenna
- Optional PCAP touch with IP69K true tested
- Optional IP67 solution



Main System

CPU	FCBGA1023 3rd Generation Intel® Core i7/i5/i3/Celeron processor (17W max.)
Chipset	Intel® HM65
Graphics	Intel® integrated HD Graphics 4000
Memory	Two 1333 / 1600 MHz DDR3 SODIMM socket support dual Channel, non-ECC, up to 16GB

LCD Panel

Size	15" 4:3
Resolution	1024 x 768 (XGA)
Color numbers	16.7M colors (RGB 6bit + HiFRC)
Viewing angle	160 (H) / 160 (V)
Contrast	600:1
Brightness	450 nits

Touch Panel

Type	Full Flat Resistive touch, 5-wire
Light transmission	80±5%
Hardness	4H
Life time	490,000 hours

Storage & Expansion

HDD	2.5" SATA HDD drive bay x 1
Expansion slot	Mini PCIe x 2

I/O & Power & Control Keys

USB	1 x M12 8pin for USB 1/2 1 x M12 8pin for USB 3/4
COM	1 x M12 8pin for COM 1/RS-232 1 x M12 8pin for COM 2/RS-232
LAN	1 x M12 8pin for LAN 1
Power input	1 x M12 5pin DC power connector, DC7V~32V
Power adaptor	AC 90 ~ 264V / 47 ~ 63 Hz / DC output 12V, IP67, 60W
Power consumption	45.8 W (MAX. Loading without adapter)
Control keys	Rear bottom: Power on/off


Mechanical & Environmental

Housing	Stainless steel (SUS304), chassis type
IP rating	IP66 whole set (include the I/O connectors & control keys)
Cooling	Fanless
Dimension	395 x 309.5 x 58 mm (W x H x D, not include I/O connectors)
Weight (net)	8.4 Kg (net)
Temperature	12V DC Input 0~40°C (IEC60068-2-56, air flow cooling) Storage - -20°C~60°C
Humidity	Operating & storage - 10%~90%, non-condensing
Regulatory	FCC, CE (EMC), VCCI Class B

Ordering Information

WTP-9A66-15 (i5)	15" FANLESS	Core i5-3317U / 4G RAM / 500G HDD / Full flat R-Touch
WTP-9A66-15 (i7)	15" FANLESS	Core i7-3517U / 4G RAM / 500G HDD / Full flat R-Touch

Outline Drawing




Options

Wireless or Wireless + BT kit (2 Dipole ant)
M12 to 1x COM cable (cable length is 2 meters)
M12 to 1x USB cable (1 USB Port) (cable length is 2 meters)
M12 to 2x USB cable (2 USB Port) (cable length is 2 meters)
M12 to 1x LAN cable (cable length is 2 meters)
SSD
Wall mount / table mount bracket
Wireless or Wireless and BT kit (easy clean and Robust Antenna)
Full flat PCT touch screen IP69K
IP67
2 External LAN (USB x2, LAN x2, COM x1)
SUS316 enclosure

Customization

1000 nits high brightness LCD
Sunlight readable optical bonding
LCD Auto dimming
LCD Super dimming (Low brightness)
USB 3.0
Second HD
Intel Core i7-3517U
5W/2W speaker
Barcode reader
COM+power 5V or 12V
LCD 450 nits
TPM



- 1 Giga LAN
- 2 USB 1/2
- 3 USB 3/4
- 4 COM x 2
- 5 DC-in
- 6 Power on/off

