


POS Printer (Option)

DISPLAY



UNDER DEVELOPMENT



RP-F10 + LCD (Option)



Display (Vertical)



Display (Horizon)

- 4.3inch TFT LCD (W480 x H272 pixels)
- Various installation methods :
Built-in printer (RP-F10), Stand-alone, Fixing screw (wall mount)
- Various display contents :
Character, Barcode (1D Barcode / QR code) Image (JPEG, PMG)
- Various applications :
Customer display, QR payment, Advertisement
- Printer error and its recovery method are displayed (Connect with RP-F10)
- Various drivers and wide variety utility software

Model		DISPLAY
LCD	Panel Size	4.3 inch
	Method	TFT LCD
	Color	16 Bit Color
	Number of Pixels (pixel)	480 (W) x 272 (H)
	Active Area (mm)	95.04 (W) x 53.856 (H)
	Pixel Pitch (mm)	0.198 (W) x 0.198 (H)
	Luminance (cd/m ²)	300
Contents		Character, Barcode, Image
Character	Character matrix (H x W pixel)	24 x 12, 24 x 24, 16 x 8, 16 x 16
	Character size (H x W mm)	4.752 x 2.376, 4.752 x 4.752, 3.168 x 1.584, 3.168 x 3.168
	Number of characters	ANK : 320 characters (40 characters x 8 lines) Kanji : 160 characters (20 characters x 8 lines)
	Character type	Code page (18Page), International character, Optional font (max. 255 x 255 pixel), JIS 1&2 Level Kanji Special character, User-defined character
	Character decoration	Vertical double (x2, x4), Horizontal double (x2, x4), Bold, Underlin
Barcode	1D	UPC-A/E, JAN (EAN) 8/13, ITF, CODABAR, Code39, Code128
	2D	QR code (Version 1 - 22, Cell size 1 - 16 pixel)
Image		JPEG, PNG
Power supply		DC 4.75 V - 5.25 V (Activated with USB bus power)
Communication interface		USB 2.0 Full speed, micro B connector
Operating Temperature (°C)		5 - 45
Service life		30,000 hours
Dimensions (W x D x H mm)		TBD
Mass (g)		TBD
Standard		FCC, CE, VCCI
Display tilt angle		0 - 150°
Installation method		Built-in printer (RP-F10), Stand-alone, Fixing screw (wall mount)
Software		Windows® : OPOS Driver, POS for .Net Driver / SDK / Utility Android™ : SDK / Utility

Windows® is the registered trademark of Microsoft Corporation(USA).
Android™ is a trademark of Google Inc.
This product is under development. The specs are subject to change.

Printed in Feb. 2019



Seiko Instruments Inc.
Print System Div.
8, Nakase 1-chome, Mihama-ku
Chiba-shi, Chiba 261-8507, Japan
Telephone: +81-43-211-1106 Facsimile: +81-43-211-8037
Homepage: <http://www.sii-ps.com>

Seiko Instruments U.S.A., Inc.
21221 S. Western Ave., Suite 250, Torrance, CA 90501, USA.
Telephone: +1-310-517-7778 Facsimile: +1-310-517-7779
Homepage: <http://www.siiprinters.com>

Seiko Instruments GmbH
Siemensstrasse 9 D-63263 Neu-Isenburg, Germany
Telephone: +49-6102-297-0 Facsimile: +49-6102-297-222
E-mail: info@seiko-instruments.de
Homepage: <http://www.seiko-instruments.de>

