

Fanned BOX



## KEY FEATURES

- AMD Ryzen™ 5000U-Series  
(4X4 BOX-5800U/4X4 BOX-5600U/4X4 BOX-5400U)
- 2 x 260-pin SO-DIMM up to 64GB DDR4 3200 MHz
- 3 x USB 3.2 Gen2, 2 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E(WiFi-6E), 1 x SATA3
- 1 x Realtek 1 Gigabit LAN (support DASH), 1 x Realtek 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.0a, 3 x DP 1.2a (2 from Type C)
- TPM 2.0 onboard IC
- 19V/90W Power Adapter
- 110.0 x 117.5 x 47.85mm, Fanned Barebone

## SPECIFICATIONS

### Processor System

CPU	4X4 BOX-5800U (AMD Ryzen™ 7 5800U, 8Cores, Max Speed up to 4.4GHz) 4X4 BOX-5600U (AMD Ryzen™ 5 5600U, 6Cores, Max Speed up to 4.2GHz) 4X4 BOX-5400U (AMD Ryzen™ 3 5400U, 4Cores, Max Speed up to 4.0GHz)
Chipset	SoC
BIOS	AMI SPI 128 Mbit

### Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

### Graphics

Controller	AMD Radeon™ Graphics
HDMI	HDMI 2.0a Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.2a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Max 4 display (Included 2 outputs from Type C)

### Expansion Slot

M.2/WLAN	1 x Wi-Fi 6E 802.11ax + BT 5.2 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless) * WiFi throughput speed depends on actual environment and equipment.
Bluetooth	5.2

### Audio

Interface	Realtek ALC233, High Definition Audio.
-----------	--

### Ethernet

Controller/ Speed	LAN1: Realtek RTL8125BG with 10/100/1000/2500 Mbps LAN2: Realtek R8111FPV with 10/100/1000 Mbps, support DASH function
Connector	2 x RJ-45

### Storage

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe x4 and SATA3 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

### Front I/O

USB	1 x USB 3.2 Gen2 (Type A) 2 x USB 3.2 Gen2 (Type C, Supports DP1.2a display output)
Audio	1 (headphone & microphone jack)

### Rear I/O

HDMI	1 x HDMI 2.0a
DisplayPort	1 x DP1.2a
Ethernet	1 x 1 Gigabit LAN, 1 x 2.5 Gigabit LAN
USB	2 x USB 2.0
DC Jack	1

### Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

### Power Requirements

Input PWR	1 x 19V/90W Power Adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

### Environment

Operating Temp	0°C ~ 40°C
Storage Temp	-40° C – 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

### Mechanical

Construction	Plastic
Mounting	VESA mounting
Dimensions (W x D x H)	110.0 x 117.5 x 47.85mm
Weight	Net Weight: 1kg

### Others

OS Support	Windows 10/11
TPM	TPM 2.0 onboard IC
Certifications	CE, FCC Class A
Packing List	1 x 19V/90W Power Adapter 1 x Screw Package 1 x VESA mounting bracket 1 x Bracket for M.2 2280 support