



KEY FEATURES

- Intel® Alder Lake-N SoC Processor N97
- 1 x 260-pin SO-DIMM up to 16GB DDR4 3200 MHz
- 6 x USB 3.2 Gen2, 1 x M.2 Key E, 1 x M.2 Key M, 1 x SATA3
- 2 x Realtek 2.5 Gigabit LAN
- Supports Triple display, 2 x HDMI 2.0b, 2 x DP 1.4a (From Type C)
- TPM 2.0 onboard IC
- 19V/65W Power Adapter
- 135x110x44.5mm, Fanless Embedded BOX PC

SPECIFICATIONS

Processor System

CPU	Intel® Alder Lake-N SoC Processors
Chipset	iBOX-N97(N97, QC, Max Speed Up to 3.6GHz, 12W)
BIOS	SoC
	AMI SPI 256 Mbit

Memory

Technology	Single Channel DDR4 3200 MHz
Capacity	16GB
Socket	1 x 260-pin SO-DIMM

Graphics

Controller	Intel® UHD Graphics
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Triple-Display (Included 2 outputs from Type-C)

Expansion Slot

M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0
-----	---

Audio

Interface	Realtek ALC256, High Definition Audio.
-----------	--

Ethernet

Controller/ Speed	Realtek RTL8125BG with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

Storage

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe Gen3 x1 and SATA3 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

Front I/O

USB	2 x USB 3.2 Gen2 (Type-A) 2 x USB 3.2 Gen2 (Type-C, 5V/3A, Supports DP 1.4a display output)
Audio	1 (headphone & microphone jack)

Rear I/O

HDMI	2 x HDMI 2.0b
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	1 x 19V/65W Power Adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	-20°C ~ 45°C (With extended temp. peripherals)
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

Mechanical

Construction	Aluminum housing
Mounting	VESA mounting, Wall mounting, Din-rail (By request)
Dimensions (W x D x H)	135 x 110 x 44.5mm
Weight	Net Weight: 0.7kg

Others

OS Support	Windows 10/11
TPM	TPM 2.0 onboard IC
Certifications	CE, FCC Class A
Packing List	1 x 19V/65W Power Adapter 1 x Screw Package 1 x Wall mounting kit