



## KEY FEATURES

- Intel® Core Processors Series 3 (Wildcat Lake -U)
- 1 x 262-pin SO-DIMM DDR5 6400MHz up to 64GB, supports In-Band ECC
- 2 x USB3.2 Gen2x2, 3 x USB3.2 Gen1, 2 x M.2 Key M, 1 x M.2 Key E
- 1 x Intel 2.5 Gigabit LAN, 1 x Realtek 2.5 Gigabit LAN
- Supports Triple display, 2 x HDMI 2.1, 2 x DP 1.4a (from Type-C)
- Intel® PTT
- 19V/90W Power Adapter
- 117.5 x 110.0 x 49mm (4.63" x 4.33" x 1.93"), Fanned Barebone

## SPECIFICATIONS

### Processor System

CPU	Intel® Core Processors Series 3 (Wildcat Lake -U) NUC BOX-320 (Core™ 5 320, 2P+4LPE) NUC BOX-304 (Core™ 3 304, 1P+4LPE) <small>*All CPU sku can support In-Band ECC</small>
Chipset	MCP
BIOS	AMI SPI 256 Mbit

### Memory

Technology	Single Channel DDR5 6400 MHz
Capacity	64GB
Socket	1 x 262-pin SO-DIMM

### Graphics

Controller	Intel® Graphics
HDMI	HDMI 2.1 Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 2.1/ 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Max 3 display (Included 2 outputs from Type-C)

### Expansion Slot

M.2/ WLAN	1 x Wi-Fi 6E 802.11ax + BT 5.3 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless)
-----------	---

### Audio

Interface	Realtek ALC256, High Definition Audio
-----------	---------------------------------------

### Ethernet

Controller/ Speed	LAN1: Intel® I226V with 10/100/1000/2500 Mbps LAN2: Realtek RTL8125BG with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

### Storage

M.2	1 x M.2 (KEY M, 2242) with PCIe Gen4 x1 for SSD 1 x M.2 (KEY M, 2242/2280) with PCIe Gen4 x2 for SSD
RAID	**supported by identical interface (PCIe) PCIe interface: 2*M.2 Key M

### Front I/O

USB	1 x USB 3.2 Gen1 (Type-A) 2 x USB3.2 gen2x2 (Type-C, 5V/3A, Supports DP1.4a display output)
Audio	1 (headphone & microphone jack)

### Rear I/O

HDMI	2 x HDMI 2.1
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1

### Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

### Power Requirements

Input PWR	12V~24V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

### Environment

Operating Temp	0 °C ~ 40 °C
Storage Temp	-40 °C ~ 85 °C
Operating Humidity	5% ~ 90% (non-condensing)
Storage Humidity	5% ~ 90% (non-condensing)

### Mechanical

Mounting	VESA mount
Dimensions (L x W x H)	117.5 x 110.0 x 49mm (4.63" x 4.33" x 1.93")
Weight	Net Weight: 1.0Kg

### Others

OS Support	Windows 10/11
TPM	Intel® PTT
Certifications	CE, FCC
Packing List	1 x 19V/90W Power Adapter 1 x VESA mount bracket