NUC CORE 300 BOX Series

Fanned Embedded BOX PC

ASRock Industrial







KEY FEATURES

- Intel® Core Processors Series 3 (Wildcat Lake -U)
- 1 x 262-pin SO-DIMM DDR5 6400MHz up to 64GB, supports In-Band ECC
- 2 x USB3.2 Gen2X2, 3 x USB3.2 Gen1, 2 x M.2 Key M, 1 x M.2 Key E
- 1 x Intel 2.5 Gigabit LAN, 1 x Realtek 2.5 Gigabit LAN
- Supports Triple display, 2 x HDMI 2.1, 2 x DP 1.4a (from Type-C)
- Intel® PTT
- 19V/90W Power Adapter
- 117.5 x 110.0 x 49mm (4.63" x 4.33" x 1.93"), Fanned Barebone

SPECIFICATIONS

Processor System

CPU	Intel® Core Processors Series 3 (Wildcat Lake -U) NUC BOX-320 (Core™ 5 320, 2P+4LPE) NUC BOX-304 (Core™ 3 304, 1P+4LPE) *All CPU sku can support In-Band ECC
Chipset	MCP
BIOS	AMI SPI 256 Mbit

Memory

Technology	Single Channel DDR5 6400 MHz
Capacity	64GB
Socket	1 x 262-pin SO-DIMM

Graphics

Controller	Intel® Graphics
HDMI	HDMI 2.1 Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 2.1/ 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Max 3 display (Included 2 outputs from Type-C)

Expansion Slot

M.2/ WLAN	1 x Wi-Fi 6E 802.11ax + BT 5.3 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless)

Audio

Interface	Realtek ALC256, High Definition Audio

Ethernet

Controller/ Speed	LAN1: Intel® I226V with 10/100/1000/2500 Mbps LAN2: Realtek RTL8125BG with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

Storage

M.2	1 x M.2 (KEY M, 2242) with PCIe Gen4 x1 for SSD 1 x M.2 (KEY M, 2242/2280) with PCIe Gen4 x2 for SSD
RAID	**supported by identical interface (PCIe) PCIe interface: 2*M.2 Key M

Front I/O

USB	1 x USB 3.2 Gen1 (Type-A) 2 x USB3.2 gen2x2 (Type-C, 5V/3A, Supports DP1.4a display output)
Audio	1 (headphone & microphone jack)

Rear I/O

HDMI	2 x HDMI 2.1
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	12V~24V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0 °C ~ 40 °C
Storage Temp	-40 °C ~ 85 °C
Operating Humidity	5% ~ 90% (non-condensing)
Storage Humidity	5% ~ 90% (non-condensing)

Mechanical

Mounting	VESA mount
Dimensions (L x W x H)	117.5 x 110.0 x 49mm (4.63" x 4.33" x 1.93")
Weight	Net Weight: 1.0Kg

Others

OS Support	Windows 10/11
TPM	Intel® PTT
Certifications	CE, FCC
Packing List	1 x 19V/90W Power Adapter 1 x VESA mount bracket

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.