



KEY FEATURES

- Intel® Core™ Ultra processors (Arrow Lake-H)
- 2 x 262-pin CSO-DIMM DDR5 6400MHz up to 96GB (48GB per DIMM)
- 1 x USB4/Thunderbolt™4, 5 x USB 3.2 Gen2, 2 x M.2 Key M, 1 x M.2 Key E (WiFi-6E Module)
- 1 x Intel 2.5 Gigabit LAN
- Supports Quad display, 2 x HDMI 2.1 TMDS, 1 x DP 2.1 (from Type-C), 1 x DP 1.4a (from Type-C)
- Intel® PTT
- Supports Intel® vPro, VMD RAID 0/1
- 19V Power Adapter
- 117.5 x 110.0 x 38mm(4.63" x 4.33" x 1.50"), Slim Type Fanned Barebone

SPECIFICATIONS

Processor System	
CPU	Intel® Core™ Ultra processors (Arrow Lake-H) NUCS BOX-255H (Ultra 7 255H, 6P+8E) NUCS BOX-225H (Ultra 5 225H, 4P+8E)
Chipset	MCP
BIOS	AMI SPI 256 Mbit
Memory	
Technology	Dual Channel DDR5 6400 MHz
Capacity	96GB (48 GB per DIMM)
Socket	2 x 262-pin SO-DIMM
Graphics	
Controller	Intel® Arc™ Graphics
HDMI	HDMI 2.1 TMDS Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a/2.1, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Quad-Display (Included 2 outputs from Type-C)

Expansion Slot	
M.2/ WLAN	1 x Wi-Fi 6E 802.11ax + BT 5.3
Audio	
Interface	Realtek ALC256, High Definition Audio.
Ethernet	
Controller/ Speed	Intel® I226LM with 10/100/1000/2500 Mbps
Connector	1 x RJ-45
Storage	
M.2	1 x M.2 (KEY M, 2280) with PCIe Gen4x4 for SSD 1 x M.2 (KEY M, 2242) with PCIe Gen4x1 for SSD
RAID	Intel® VMD RAID 0/1 **supported by identical interface (PCIe) PCIe interface: 2*M.2 Key M
Front I/O	
USB	2 x USB 3.2 Gen2 (Type A) 1 x USB4/Thunderbolt™ 4 (Supports DP2.1 display output) 1 x USB3.2 Gen2x2 (Type-C, Supports DP1.4a display output) *For Thunderbolt support, please refer to support list.
Audio	1 (headphone & microphone jack)
Rear I/O	
HDMI	2 x HDMI 2.1 TMDS
Ethernet	1 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1
Watchdog Timer	
Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec
Power Requirements	
Input PWR	12V~24V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready
Environment	
Operating Temp	0°C ~ 40°C
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%
Mechanical	
Mounting	VESA mount
Dimensions (L x W x H)	117.5 x 110.0 x 38mm(4.63" x 4.33" x 1.50")
Weight	Net Weight:1.0Kg
Others	
OS Support	Windows 10/11
TPM	Intel® PTT
Certifications	CE, FCC
Packing List	1 x 19V/120W Power Adapter (Core Ultra 7) 1 x 19V/90W Power Adapter (Core Ultra 5) 1 x VESA mount bracket