


SBC-374

3.5"SBC Motherboard



KEY FEATURES

- Intel® Core™ Ultra Processors (Meteor Lake-PS)
- 1 x 262-pin SO-DIMM DDR5 5600 MHz, up to 48GB
- 1 x USB 3.2 Gen2x2, 2 x USB 3.2 Gen2, 6 x USB 2.0, 1 x M.2 Key E, 1 x M.2 Key M, 2 x COM, 1 x SATA3
- 1 x Intel 2.5 Gigabit LAN, 1 x Intel 1 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.1 TMDS, 2 x DP 1.4a (1 from Type-C), 1 x LVDS or eDP
- TPM 2.0 onboard IC
- Support Intel® vPro
- 12~28V DC-In

SPECIFICATIONS

Form Factor

Dimensions	3.5"SBC (5.8-in x 4-in x 1.09-in, 14.7 cm x 10.2 cm x 2.77 cm)
------------	--

Processor System

CPU	Intel® Core™ Ultra Processors (Meteor Lake-PS), up to 45W
Socket	LGA 1851
BIOS	AMI SPI 256 Mbit
Secure Flash	AMI SPI 32Mbit (Optional)

Memory

Technology	Single Channel DDR5 5600 MHz
Capacity	48GB
Socket	1 x 262-pin SO-DIMM

Graphics

Controller	Intel® Xe LPG Graphics
HDMI	HDMI 2.1 TMDS Max resolution up to 4096 x 2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
LVDS	Dual channel 24 bit up to 1920 x 1200@60Hz (Connector shared with eDP)
eDP	Max resolution up to 1920 x 1080@60Hz (Connector shared with LVDS)
MultiDisplay	Quad display (Included 1 output from Type-C)

Expansion Slot

M.2	1 x M.2 (Key E, 2230) with PCIe Gen4 x1 and USB 2.0 for Wireless
-----	--

Audio

Interface	Realtek ALC256 HD, High Definition Audio.
-----------	---

Ethernet

Controller/ Speed	LAN1: Intel® I226V with 10/100/1000/2500 Mbps LAN2: Intel® I219LM with 10/100/1000 Mbps, supports vPro
Connector	2 x RJ-45

Rear I/O

HDMI	1 x HDMI 2.1 TMDS
DisplayPort	1 x DP 1.4a
Ethernet	1 x 1 Gigabit LAN 1 x 2.5 Gigabit LAN
USB	1 x USB 3.2 Gen2x2 (Type-C, 5V/3A, Support DP 1.4a display output) 2 x USB 3.2 Gen2 2 x USB 2.0

Internal Connector

USB	4 x USB 2.0 (2 x 2.00 pitch header)
COM	COM1, COM2 (RS-232/422/485)
GPIO	4 x GPI, 4 x GPO
LVDS	1 (Connector with LVDS/eDP signal, switch by BIOS)
Speaker Header	1
MIPI Camera Header	1

Storage

M.2	1 x M.2 (Key M, 2242/2280) with PCIe Gen4 x4 for SSD
SATA	1 x SATA3 (6Gb/s)

Security

TPM	TPM 2.0 onboard IC
-----	--------------------

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	12~28V DC-In with 4-pin wafer PWR
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	-20°C ~ 70°C
Storage Temp	-40°C ~ 85°C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%