




# NUC EHL Motherboard Series

NUC-J6412/NUC-J6413/NUC-J6426/NUC-N6210/NUC-N6211/NUC-N6415



## KEY FEATURES

## NUC Motherboard

- Intel® ElkHart Lake SoC Processors
- 2 x 260-pin SO-DIMM DDR4 3200 MHz, up to 32GB
- 4 x USB 3.2 Gen2, 4 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E, 1 x COM, 1 x SATA3
- 2 x Realtek 1 Gigabit LAN
- Supports Dual display, 1 x HDMI 2.0b, 1 x DP 1.4
- TPM onboard
- 12V~19V DC-In

## SPECIFICATIONS

### Form Factor

Dimensions	NUC (4.09-in x 4.02-in)
------------	-------------------------

### Processor System

CPU	Intel® ElkHart Lake SoC Processors NUC-J6412 (J6412, QC, Max Speed up to 2.6GHz, 10W) NUC-J6413 (J6413, QC, Max Speed up to 3.0GHz, 10W) NUC-J6426 (J6426, QC, Max Speed up to 3.0GHz, 10W) NUC-N6210 (N6210, DC, Max Speed up to 2.6GHz, 6.5W) NUC-N6211 (N6211, DC, Max Speed up to 3.0GHz, 6.5W) NUC-N6415 (N6415, QC, Max Speed up to 3.0GHz, 6.5W)
Chipset	SoC
BIOS	AMI SPI 256 Mbit

### Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	32GB (16 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

### Graphics

Controller	Intel® Gen 11 Graphics
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Max 2 display

### Expansion Slot

M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0
-----	---

### Audio

Interface	Realtek ALC233, High Definition Audio.
-----------	--

### Ethernet

Controller/ Speed	Realtek RTL8111G with 10/100/1000 Mbps
Connector	2 x RJ-45

### Front I/O

USB	1 x USB 3.2 Gen2 (Type-A) 2 x USB 3.2 Gen2 (Type-C)
Audio	1 (headphone & microphone jack)

### Rear I/O

HDMI	1 x HDMI 2.0b
DisplayPort	1 x DP1.4
Ethernet	2 x 1 Gigabit LAN
USB	1 x USB 2.0 1 x USB 3.2 Gen2 (Type-A)
DC Jack	1

### Internal Connector

USB	2 x USB 2.0 (1 x 2.00 pitch header)
COM	1 x COM(RS232/422/485)
TPM	Infineon SLB9670VQ2.0

### Storage

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe x1 and SATA3 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

### Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

### Power Requirements

Input PWR	12V~19V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

### Environment

Operating Temp	0°C ~ 60°C
Storage Temp	-40°C ~ 85°C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%