

IVS-110-AL

Vehicle Fleet Management System

Features

- Intel® Apollo Lake processor
- Dual SIM slot
- Optional 3G/Wi-Fi
- 16 x DI/DO
- 1 x HDMI (lockable), 1 x VGA
- Built-in GPS function
- E-Mark certification
- Built-in OBD-II/J1939
- IP4X protection



Specifications

Model		IVS-110-AL
Chassis	Color	Black
	Dimensions (WxDxH) (mm)	261 x 170 x 60
	System Fan	Fanless
	Chassis Construction	Extruded aluminum alloy
Motherboard	CPU	Intel® Atom™ x7-E3950 1.6 GHz (up to 2.0 GHz, quad-core, TDP 12W)
	Chipset	SoC
	System Memory	1 x SO-DIMM DDR3L 1600/1866 (4GB pre-installed)(up to 8GB)
Storage	Hard Drive	1 x 2.5" SATA 6Gb/s HDD/SSD bay
	eMMC	1 x eMMC5.0 (optional)
Communication	WLAN	802.11 a/b/g/n/ac (optional)
	Bluetooth	BT 4.0/3.0+HS (optional)
	WWAN	WCDMA/HSDPA/HSUPA (optional)
	GPS	On-board GPS
I/O Interfaces	USB	4 x USB 3.2 Gen1
	Ethernet	1 x RJ-45: 1 x GbE by Intel® I210
	COM Port	1 x RS232/422/485 with AFC (DB9)
	Digital I/O	16-bit Digital I/O (8-in/ 8-out)
	OBD-II	1 x OBD-II/J1939 (DB9)
	Display	1 x HDMI (up to 3840 x 2160@30Hz) 1 x VGA (up to 1920 x 1600@60Hz)
	Audio	1 x Line-out
	Antenna	1 x 3G, 1 x GPS, 1 x BT, 1 x Wi-Fi
	Other	1 x Power Button, 1 x LED for HDD, 1 x LED for Wi-Fi, 2 x LED for SIM
Expansions	PCIe Mini	1 x Full/Half-size with SIM card slot (PCIe/USB 2.0) 1 x Full/Half-size with SIM card slot (PCIe/USB 2.0) 1 x Half-size (PCIe/USB 2.0)
Power	Power Input	Cigarette lighter power cable: 9 ~ 36V DC
	Power Consumption	12V @ 5A (Intel® x7-E3950 with 8GB memory)
Reliability	Mounting	Wall-mount/ VESA 100
	Operating Temperature	-30 ~ 70°C with air flow (SSD), 10% ~ 95% non-condensing
	Storage Temperature	-40 ~ 80°C with air flow (SSD), 10% ~ 95% non-condensing
	Operating Shock	Half-sine wave shock 5G, 11ms, 100 shocks per axis (SSD)
	Operating Vibration	MIL-STD-810F 514.5C-2 (SSD)
	Weight (Net/Gross)	2.4KG/ 3.8KG
	Safety/EMC	CE/ FCC/ E-Mark
	IP Rating	IP 4X compliant
	Watchdog Timer	Programmable 1 ~ 255 sec/min
OS	Supported OS	Microsoft® Windows 10


Fleet Management Tracking System





Fully Integrated I/O

Dimensions (Unit: mm)

Front view



Side view



IVS-110-AL

Ordering Information

Part No.	Description
IVS-110-AL-E3/4G-R10	Fanless embedded system with Intel® Atom™ x7-E3950 (12W) Processor with 4GB DDR3L pre-installed memory, on-board GPS, HDMI, VGA, one GbE LAN, one 2.5" SATA HDD bay, two SIM slots, RoHS

Options

Item	Part No.	Description
GPS/LTE antenna	32506-000400-100-RS	Integration Antenna, Magnetic Antenna Base+GPS/4G LTE ANTENNA, RG 174, 5000MM, AU-4S-LTE, GPS Gain:27dB, LTE, Gain:0dBi, 50Ω, SANAV, 1575.42MHz/704-960MHz/1710-2766MHz, VSWR ≤ 2.0, SMA PLUG, REVERSE SMA PLUG, RoHS
Power adapter	IVIPOWER-4PIN-R20	Power adapter with 4-pin transfer cable, RoHS
OBD-II cable	32025-003400-100-RS	Round cable, OBD-II cable, 2000 mm, 24 AWG, (A) OBD-II 16P male, (B) D-sub 9P female, one piece package with label, RoHS
Cigarette lighter power cable	32002-004000-100-RS	Round cable, power cable, car cigarette lighter cable, 2000 mm, 18 AWG, (A) cigarette lighter (5 A 250 V)+ ψ3 green LED, (B) MOLEX 5557-0400 P=4.2, SHANGHAI YING YU, RoHS
Wireless kit	IVS-WIFI-KIT02-R10	1T1R Wi-Fi module kit for embedded system, IEEE802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.0/3.0+HS, 1 x Wi-Fi module, 2 x Antenna, RoHS
WWAN kit	IVS-3G-KIT02-R10	3G module kit for embedded system, F260, 1 x 3G module, RoHS
ACC power cable	32002-001900-100-RS	Round cable, power cable, 3000 mm, 16 AWG, (A) MOLEX 5557-04P P=4.2, SHANGHAI YING YU, RoHS

Packing List

Item	Part No.	Qty	Description
Screw pack	44005-030083-RS	4	Screw pack
	42005-000603-RS	4	Screw pack
	44003-030052-RS	4	Screw pack
	44045-020031-RS	5	Screw pack
SATA cable	32801-003608-100-RS	1	Sata cable, 3, 150mm/150mm, 26AWG, SATA 7+15P female 180°, SATA 7P female 90°+lock, JST PHR-2 P=2.0, One pcs PKG W/ label, RoHS
Wall mount kit	41020-0482C2-00-RS	2	Wall mount bracket

E-Window (for ATO assembly) E-Window

Part No.	Description
E-MPCIE-LAN-R10	PCIe Mini card supports 1-port GbE with Realtek RTL8111E controller, with PMS 194C I/O bracket and 250mm cable, R10
E-MPCIE-DLAN-R10	PCIe Mini card supports 2-port GbE with Intel I211 controller, with PMS 194C I/O bracket and 250mm cable, R10
E-MPCIE-UART-KIT02-R10	PCI Express Mini supports Dual RS-232/422/485, 16-bit GPIO module, full-size, RoHS