HBJC923R3328DG2N Series


Rockchip® ARM Cortex A53 RK3328, Android 7.1




1. Rockchip® A53 RK3328 Quad-core 1.5GHz
2. Onboard 1333 /2GB DDR3L DRAM
3. 8G Flash ROM (Max. 32GB)
4. HBJC923R3328DG2NS: Support 1* GbE and 1* USB3.0
5. HBJC923R3328DG2NL: Support 1* GbE and 1* 10/100M LAN
6. Support 1* Micro SD Socket (Max 64G)
7. 2* USB2.0, 1* OTG/DC-in, 1* HDMI, 1* Line-out
8. Support Android 7.1
9. 5V DC-in

External I/O

HBJC923R3328DG2NS



HBJC923R3328DG2NL










Specifications

MB Model	JR3328-DG2N (1.8” SBC)	JR3328-DG2NL (1.8” SBC)
Part No	HBJC923R3328DG2NS	HBJC923R3328DG2NL
CPU/Chipset	● Rockchip® ARM Cortex A53 RK3328 Quad-core 1.5GHz SoC Processor	
Memory	2GB/1333MHz DDR3L	
Storage	● 8GB Flash (Max. 32GB)	
Network	● 1 * Realtek RTL8211F-CG / 10/100/1000Mbps	● 1 * Realtek RTL8211F-CG / 10/100/1000Mbps ● 1 * 10/100 Mbps internal FE PHY
Rear I/O	● 1* RJ45 ● 1* USB3.0 ● 2* USB2.0	● 2* RJ45 ● 2* USB2.0
Side I/O	● 1* HDMI (3840 x 2160@60Hz) ● 1* OTG/5V DC-in ● 1* Audio Line-out ● 1* Micro SD card socket	
Power Source	● DC 5V-3.0A ● AC 100~240V input	
Compliance	RoHS, CE, FCC, CE-LVD	
Temperature	Operating Temperature: -10 ~ 60°C Storage Temperature: -20 ~ 65 °C	
Dimensions	94.4 (W) x 60.5 (D) x 33.6 (H) mm With Shelf: 110.0 (W) x 111.1 (D) x 33.6 (H) mm	
OS Support	Android 7.1	
Warranty	2 Years limited warranty	

* Specifications subject to change without notice, not responsible for typographical errors. Does not include HDD or OS.

Mechanical Drawings (Unit = mm)



Accessories

Parts Number	Description
----------	HBJC923R3328DG2NS / HBJC923R3328DG2NL
L01ADEU01-F	Adapter 5V/3A/15W
HCS923VESA01B-W-F	VESA Mount