

11th Gen Full IP65 Box PC

Features

- Fanless and rugged housing
- 11th Gen Intel® Core™ Celeron 6305E / i3 1115G4E / i5 1145G7E / i7 1185G7E Processors
- Full IP65 304 stainless steel enclosure
- All M12 waterproof connectors with cables
- 1 x LAN, 2 x RS232/422/485, 1 x USB, 1 x HDMI
- 1 x M.2 M key, 1 x M.2 B Key, 1 x M.2 E Key for RAID 0/1 (Only i5/i7)
- Wall mount
- IIoT gateway



Specifications

Model No.	FB0103/104/105/106SW
System	
CPU	11 th Gen Intel® Core™ Celeron 6305E (103)/ i3 1115G4E(104)/ i5 1145G7E (105) / i7 1185G7E (106) Processors
Memory	
H/W Monitor	
H/W Monitor	Watch Dog Timer 256 Level
TPM	
Controller	Infineon SLB9670VQ2.0
I/O Ports	
USB	2
RS232/422/485	2 (0V/5V/12V, support auto air flow)
GLAN	1
HDMI	1
Storage	
Storage	1 x SATA 3.0
Expansion	
M.2	1 x M.2 M Key(PCI e Gen x 4 NVMe) 2280 1 x M.2 B Key (PCI e x 1 USB 2.0 with NANO SIM Holder, SATA 3.0) 2242 / 3042 1 x M.2 E Key (PCI e x 1 USB 2.0) 2230
Power Requirement	
Power Requirement	DC in 12 ~ 24V (OCP & OVP)
OS support	
OS support	Window 10 Pro / Window 10 IoT / Linux Kernel 5.4 / Ubuntu LTS
Mechanical & Environmental	
Construction	Full stainless steel enclosure with external heatsink
Operation Temp.	0 ~ 50°C
Operation Humidity	10 ~ 90%, non-condensing
Mounting	Wall mount
Dimension (WxHxD)	286 x 210 x 58 mm
Weight	TBD



Optional

P/N: 2351206003	Full IP65 Waterproof Power adaptor with European power cord (60W / 90 ~ 295V AC input / 12V DC output)
P/N: 2351206004	Full IP65 Waterproof Power adaptor with US power cord (60W / 90 ~ 295V AC input / 12V DC output)
P/N: 2340000003	1 x Full IP65 LAN port
P/N: 2390000003	external antenna (WIFI)
P/N: 3121700001	5GB LTE module with SIM socket

**Specifications are subject to change without notice.


Ordering Information

FB103SW04128	Fanless full IP65 stainless steel box PC, Intel Celeron 6305E, 4GB DDR4 So-DIMM. M.2 128GB SSD, DC in external power adapter
FB104SW04064	Fanless full IP65 stainless steel box PC, Intel i3 1115G4E, 4GB DDR4 So-DIMM. M.2 128GB SSD, DC in external power adapter
FB105SW04128	Fanless full IP65 stainless steel box PC, Intel i5 1145G7E, 4GB DDR4 So-DIMM. M.2 128GB SSD, DC in external power adapter
FB106SW04128	Fanless full IP65 stainless steel box PC, Intel i7 1185G7E, 4GB DDR4 So-DIMM. M.2 128GB SSD, DC in external power adapter

Dimension

• FB103/104/105/106SW

Unit : mm



Kingdy Technology Inc.

No. 8, Ln. 25, Zhongban Rd., Zhonghe Dist., New Taipei City 23556, Taiwan

Tel : +886-2-3234-6288

Fax : +886-2-3234-3199

E-mail : sales@kingdy.com.tw

www.kingdy.com.tw

